

POWER PACKAGE


UMBRA

THE UMBRA POWER PACKAGE delivers a complete, integrated power solution for small satellites. Combining a high-efficiency, body-steered deployable solar array, high-density battery modules, and intelligent power management, it provides reliable power for demanding LEO missions. Flight-proven components, Falcon 9 heritage, and a compact design ensure mission success. Choose Umbra for a streamlined, high-performance power subsystem.

POWER EFFICIENCY | COMPACT FOOTPRINT | MORE THAN 5YR MISSION LIFE | LEO ENVIRONMENT | FLIGHT PROVEN









FEATURES

EASY | GENERATION, STORAGE & MANAGEMENT

The Umbra Power Package provides a complete, pre-integrated power subsystem, combining solar power generation, high-density energy storage, and intelligent power management. This integrated approach simplifies procurement, reduces integration complexity, and optimizes system-level performance.

COMPACT POWER | SIMPLE INTEGRATION

Featuring a high-efficiency, body-steered deployable (BSD) solar array and high-energy-density lithium-ion battery modules, the system delivers robust and reliable power. Body-steering removes the need for a solar array drive, while the batteries ensure continuous operation through eclipse and peak demand periods.

FLIGHT-PROVEN | VALIDATED RELIABILITY


Successfully flown on Falcon 9 rideshare missions to LEO, the solar array, battery, and HDRM offer proven reliability. This flight heritage reduces mission risk and provides assurance of dependable performance in real-world space environments.

LOW SWaP | REDUCE FOOTPRINT

Engineered for small satellite applications, the Power Package optimizes SWaP (Size, Weight, and Power) through its compact and lightweight design. The high stowage efficiency of the array and the high energy density of the batteries minimize the system's footprint, maximizing available payload volume.

DATA SHEET 5101D0002 REV 02
PART 5101H10001-1
VALID AS OF 03.20.2026

STOWED ARRAY



BATTERY



PMU



GENERAL SPECIFICATIONS

BUS VOLTAGE RANGE	28 V ± 4V
BUS VOLTAGE NOMINAL	28 V
PEAK POWER	**Single Array:** 120 W generation BOL **Dual Array:** 240W generation BOL
AVERAGE POWER	N/A
ELECTRICAL INTERFACE	Power Umbilical Inhibits TT&C
DATA INTERFACE	RS-422
INTENDED SPACE ENVIRONMENT	LEO
HERITAGE	In combination: Individual component designs flown on Umbra 1-10, combined and repackaged for customer product
DESIGN LIFE	5+ Years
PRODUCTION	Assembled and tested in the USA

ENVIRONMENTAL SPECIFICATIONS

RANDOM VIBE	Qualified to 14.16 G_{rms} profile enveloping GEVS, Falcon 9, SpaceX Rideshare, and Electron levels
SHOCK	Qualified to 1000g peak profile enveloping GEVS, Falcon 9, SpaceX Rideshare, and Electron levels
OPERATING TEMPERATURE	Solar Array & HDRMS: -50°C to 90°C
SURVIVAL TEMPERATURE	Solar Array & HDRMS: -60°C to 120°C
TOTAL IONIZING DOSE DESIGN CAPABILITY	Designed to withstand at least 30 krad TID

CONFIGURATIONS

TYPE	DESCRIPTION & DETAILS	SPACE READY	TYPICAL LEAD TIME	COST
EDU	• Battery Modules: Not Space Rated • Power Management Unit: Not Space Rated	No	< 6 Weeks	CONTACT
FLIGHT	• Default flight configuration (as described in this data sheet) • Umbra Steered Deployable Solar Array-120: **1x** • Umbra Battery Module-8S2P: **2x** • Umbra Power Management Unit: **1x** • Umbra Hold Down and Release Mechanism: **1x**	Yes	< 18 Weeks	CONTACT

UMBRA
https://umbra.space/space-systems
space.systems@umbra.space